

FH-KM

***STIHL***



2 - 14      Instruction Manual



## Contents

1	KombiSystem.....	2
2	Guide to Using this Manual.....	2
3	Safety Precautions and Working Techniques.....	2
4	Using the Unit.....	5
5	Approved KombiEngines.....	6
6	Mounting the KombiTool.....	6
7	Assembling the Unit.....	6
8	Adjusting the Cutter Bar.....	8
9	Fitting the Harness.....	9
10	Starting / Stopping the Engine.....	10
11	Lubricating the Gearbox.....	10
12	Storing the Machine.....	11
13	Maintenance and Care.....	11
14	Sharpening Instructions.....	11
15	Minimize Wear and Avoid Damage.....	12
16	Main Parts.....	12
17	Specifications.....	12
18	Maintenance and Repairs.....	13
19	Disposal.....	13
20	EC Declaration of Conformity.....	13
21	UKCA Declaration of Conformity.....	14
22	Addresses.....	14

## 1 KombiSystem

In the STIHL KombiSystem a number of different KombiEngines and KombiTools can be combined to produce a power tool. In this instruction manual the functional unit formed by the KombiEngine **and** KombiTool is referred to as the power tool.

Therefore, the separate instruction manuals for the KombiEngine and KombiTool should be used together for the power tool.

Always read and and make sure you understand **both** instruction manuals before using your power tool for the first time and keep them in a safe place for future reference.

## 2 Guide to Using this Manual

### 2.1 Pictograms

All the pictograms attached to the machine are shown and explained in this manual.

## 2.2 Symbols in text



**WARNING**

Warning where there is a risk of an accident or personal injury or serious damage to property.

*NOTICE*

Caution where there is a risk of damaging the machine or its individual components.

## 2.3 Engineering improvements

STIHL's philosophy is to continually improve all of its products. For this reason we may modify the design, engineering and appearance of our products periodically.

Therefore, some changes, modifications and improvements may not be covered in this manual.

## 3 Safety Precautions and Working Techniques



Because a scrub cutter is a high-speed, fast-cutting power tool with very sharp cutting blades and a long reach, special safety precautions must be observed during operation.



Read both User Manuals (KombiEngines and KombiTools) carefully before using the unit for the first time and keep them in a safe place for future reference. Non-compliance with the User Manuals may cause serious or even fatal injury.

The power tool should only be provided or loaned to people familiar with this model and its operation. The User Manuals for KombiEngines and KombiTools should always be handed over with the machine.

Use the scrub cutter only for cutting grass, scrub, shrubs, bushes, undergrowth, groundcovers, brush and similar materials.

The machine must not be used for any other purposes – **risk of accident!**

Only use cutting blades and accessories that are explicitly approved for this power tool by STIHL or are technically identical. If you have any questions in this respect, consult your dealer.

Use only high-quality parts and accessories. In order to avoid the risk of accidents and damage to the machine.

STIHL recommends the use of genuine STIHL tools and accessories. They are specifically designed to match the product and meet your performance requirements.

Never attempt to modify your power tool in any way since this may increase the risk of personal injury. STIHL excludes all liability for personal injury and damage to property caused while using unauthorized attachments.

Do not use a high-pressure washer to clean the power tool. The solid jet of water may damage parts of the unit.

### 3.1 Clothing and Equipment

Wear proper protective clothing and equipment.



Clothing must be sturdy but allow complete freedom of movement. Wear close-fitting clothes such as a boiler suit, not a loose jacket.

Do not wear clothing which could become trapped in wood, brush or moving parts of the machine. Do not wear a scarf, necktie or jewelry. Tie up and secure long hair above your shoulders.



Wear safety boots with steel toe caps and non-slip soles.



#### WARNING



To reduce the risk of eye injuries, wear close-fitting safety glasses in accordance with European Standard EN 166 (for Canada, in accordance with standard CSA Z94). Make sure the safety glasses fit snugly.

Wear "personal" sound protection, e.g. ear defenders.

Wear a safety hard hat for thinning operations, when working in high scrub and where there is a danger of head injuries from falling objects.



Wear sturdy protective gloves made of a resistant material (e. g. leather).

STIHL offers a comprehensive range of personal protective equipment.

### 3.2 Transporting the machine

Always stop the engine.

Always attach the blade scabbard (scabbard) – even when carrying the unit short distances.

Move the cutter bar to the transport position and let it snap into position.

Carry the power tool properly balanced by the shaft – cutting blades behind you.

Avoid touching hot parts of the machine and gear housing – **risk of burns!**

By vehicle: When transporting in a vehicle, properly secure your machine to prevent tipping over, damage and fuel spillage.

### 3.3 Before starting

Check that your power tool is in safe operating condition – refer to the appropriate chapters in the User Manuals for KombiEngines and Kombi-Tools:

- Cutting blades: Correctly assembled, securely mounted and in good condition (clean, move freely, not warped), sharpened and sprayed thoroughly with STIHL resin solvent (lubricant).
- Never attempt to start the machine in the transport position (cutter bar folded against the shaft).
- Never attempt to modify the controls or safety devices.
- Keep the handles dry and clean – free from oil and dirt – this is important for safe control of the machine.
- Adjust carrying harness and handles in accordance with body height. Observe the chapter "Fitting the Harness"

The power tool must only be operated when it is in good operating condition – **Risk of accident!**

To prepare for emergencies when using a harness: Practice setting down the machine quickly. To avoid damage, do not throw the machine to the ground when practicing.


### 3.4 Holding and Guiding the Tool

Always hold the unit firmly with both hands on the handles.

Make sure you always have a secure footing and hold the machine so that the cutting blades are always facing away from your body.


Some versions of the machine can be carried on a harness to relieve the weight on the operator's arms.

### 3.4.1 Models with Loop Handle



Right hand on control handle, left hand on loop handle on the shaft, even if you are left-handed. Wrap your fingers and thumbs around the handles.

### 3.4.2 Machines with handle hose



Right hand on control handle, left hand on handle hose on drive tube, even if you are left-handed. Wrap your fingers and thumbs around the handles.

## 3.5 While Working

In the event of impending danger or in an emergency, switch off the engine immediately by moving the slide control/stop switch to **0** or **STOP**.



This power tool is not insulated. Keep away from power cables – **danger of electrocution!**



**To reduce the risk of injury from moving blades or falling cuttings**, do not allow bystanders within 5 meters of your own position.

This distance must also be maintained in relation to objects (vehicles, window panes) – **risk of property damage!**

Check for correct idling, so that the cutting blades stop moving when the throttle trigger is released. Check and correct the idle speed setting at regular intervals. If the cutting blades con-

tinue to run, have a dealer repair the machine – see User Manual for KombiEngines.

Watch the cutting blades at all times – do not cut areas of bushes or scrub that you cannot see.

Be extremely careful when cutting high scrub or bushes, check the other side before starting work.



The gearbox becomes hot during operation. Do not touch the gear housing – **risk of burns!**

Take special care in **slippery conditions** – damp, snow, ice, on slopes or uneven ground!

Clear away fallen branches, scrub and cuttings from the work area.

Watch out for obstacles: Tree stumps, roots – **risk of tripping or stumbling!**

Make sure you always have a firm and secure footing.

#### When working at heights:

- Always use a lift bucket
- Never use the machine while standing on a ladder or in a tree
- never work on an unstable surface
- Never use the machine with just one hand

Be particularly alert and cautious when wearing ear protection because your ability to hear warnings (shouts, alarms, etc.) is impaired.

Take breaks when you start getting tired or feeling fatigue – **risk of accidents!**

Work calmly and carefully – in daylight conditions and only when visibility is good. Proceed with caution, do not put others in danger.

Inspect scrub and work area to avoid damaging the cutting blades:

- Remove stones, rocks, pieces of metal and other solid objects
- Make sure that no sand or stones get between the cutting blades, for example, when working close to the ground.
- Do not touch wire with the cutting blades when cutting scrub or bushes next to or against wire fences.

Do not touch electric power lines – never cut through electric power lines – **risk of electrocution!**



Do not touch the cutting blades while the engine is running. If the cutting blades become jammed by an object, switch off the engine immediately

before attempting to remove the object – **risk of injury!**

Opening the throttle when the cutting blades are jammed increases the load and reduces the working speed of the engine. The clutch then slips continuously and this can cause overheating and damage to important components (e.g. clutch, plastic housing components) – as a result, there is a **risk of injury** from the idling cutting blades!

If your power tool is subjected to unusually high loads for which it was not designed (e.g. heavy impact or a fall), always check that it is in safe operating condition before continuing work. See also "Before Starting". Make sure the safety devices are working properly. Never use a power tool that is no longer safe to operate. In case of doubt, contact a dealer.

If the scrub or bush is very dusty or dirty, spray the blades with STIHL resin solvent from time to time during cutting. This helps reduce blade friction as well as the aggressive effects of sap and the build-up of dirt particles.

Examine the cutting blade periodically at short intervals and as soon as you notice any changes:

- Shut off the engine
- Wait for cutting blades to come to a standstill
- Check condition and secure fitting; watch out for cracks
- Ensure that the cutting blades are sharp

### 3.6 After Finishing Work

After finishing work or before leaving the power tool unattended: Shut off the engine.

Always clean dust and dirt off the machine – do not use any grease solvents for this purpose.

Spray the cutting blades with STIHL resin solvent. Run the motor briefly so that the solvent is evenly distributed.

### 3.7 Maintenance and Repairs

Service the machine regularly. Do not attempt any maintenance or repair work not described in the KombiTool and KombiEngine instruction manuals. Have all other work performed by a servicing dealer.

STIHL recommends that you have servicing and repair work carried out exclusively by an authorized STIHL servicing dealer. STIHL dealers are regularly given the opportunity to attend training

courses and are supplied with the necessary technical information.

Only use high-quality replacement parts in order to avoid the risk of accidents and damage to the machine. If you have any questions in this respect, consult a servicing dealer.

STIHL recommends the use of genuine STIHL replacement parts. They are specifically designed to match your model and meet your performance requirements.

To reduce the risk of injury, **always shut off the engine** before carrying out any maintenance or repairs or cleaning the machine.

## 4 Using the Unit

Do not use your power scythe during other people's rest periods.

The power scythe is used at ground level. As its blades operate like a mower bar, the unit is ideal for cutting scrub, thicket, reed, wild growth and hard grasses. The power scythe is particularly suitable for applications in busy areas, such as traffic islands or parks, because cuttings are not caught and thrown by the blades.

### 4.1 Disposal

Do not throw cuttings into the garbage can – they can be composted.

### 4.2 Preparations

- ▶ Set cutter bar to required angle.
- ▶ Remove the blade scabbard.
- ▶ Start the engine.
- ▶ Put on the shoulder strap.
- ▶ Attaching Machine to Shoulder Strap

## 4.3 Working Technique



Working position and method are the same as for a brushcutter: Sweep the cutter bar to and fro in an arc just above the ground.

## 5 Approved KombiEngines

### 5.1 KombiEngines

Only use KombiEngines supplied or explicitly approved by STIHL for use with the attachment.

This KombiTool may be operated only with the following KombiEngines:

KM 56 R, KM 85 R<sup>1)</sup>, KM 94 R, KM 111 R, KM 131, KM 131 R, KMA 130 R, KMA 135 R, KMA 80.0 R, KMA 120.0 R, KMA 200.0 R

### 5.2 Brushcutters with split shaft

The KombiTool can also be mounted on STIHL brushcutters with a split shaft (T-models) (basic power tools).


This KombiTool can therefore also be used on the following machine:

STIHL FR 131 T


## ! WARNING

Refer to the power tool's User Manual for how to use the barrier bar.

## 6 Mounting the KombiTool



- ▶ Push the lug (1) on the drive tube into the slot (2) in the coupling sleeve as far as stop.



When correctly installed, the red line (3) (arrow point) must be flush with the end of the coupling sleeve.

- ▶ Tighten down the star knob (4) **firmly**.

### 6.1 Removing the KombiTool


- ▶ Reverse the above sequence to remove the drive tube.

## 7 Assembling the Unit

### 7.1 Removing the Protective Cap


If a cap is fitted on the end of the KombiTool's or basic power tool's drive tube:

<sup>1)</sup> Only outside the EU



413BA014 KN

- ▶ Pull the protective cap off the end of the drive tube and keep it in a safe place.




002BA248 KN

If the plug comes out of the drive tube when you pull off the cap:

- ▶ Push the plug into the drive tube as far as stop.


## 7.2 Mounting the Gearbox



0000-GXX-1681-A0

- ▶ Loosen the clamp screws (10).

- ▶ Push the gearbox (11) onto the drive tube (5), turn the gearbox (11) back and forth as necessary.




0000-GXX-1682-A0

Once the end of the drive tube is inserted beyond the slot in the clamp (12):

- ▶ Push the gearbox (11) fully home as far as stop.
- ▶ Tighten down the clamp screws moderately.
- ▶ Line up the gearbox (11) with the powerhead.
- ▶ Tighten down the clamp screws firmly.

## 8 Adjusting the Cutter Bar

### 8.1 Angle Adjuster - 145°



The angle of the cutter bar can be adjusted upwards in 4 stages from 0° (straight) to 55°, and downwards in 7 stages from 0° to 90° (right angle facing down). There are therefore 12 possible working positions.

**!** WARNING


**To reduce the risk of injury**, carry out the adjustment only when the cutting blades are at a standstill – engine at idle speed.

**!** WARNING

The gearbox gets hot during operation. **To reduce the risk of burn injury**, do not touch the gearbox.


**!** WARNING

**To reduce the risk of injury**, never touch the blades while making adjustments.



- ▶ Pull back the sliding sleeve (1) and use the lever (2) to adjust the joint by one or several holes.
- ▶ Release the sliding sleeve (1) and make sure the lock pin engages the quadrant (3).

### 8.2 Transport Position




The cutter bar can be folded flat against the drive tube and locked in position to save space during transportation.

**!** WARNING

**To reduce the risk of injury**, always shut off the engine – depress stop switch – and fit the blade scabbard before moving the cutter bar to the transport position or from the transport position to the normal working position.

**!** WARNING

The gearbox gets hot during operation. **To reduce the risk of burn injury**, do not touch the gearbox.




- ▶ Shut off the engine.
- ▶ Fit the blade scabbard.
- ▶ Pull back the sliding sleeve (1) and use the lever (2) to swing the joint upwards – in direction of drive tube – until the cutter bar is flat against the drive tube.
- ▶ Release the sliding sleeve (1) and make sure the lock pin engages the quadrant (3).

## 9 Fitting the Harness


The type and style of the harness and carabiner (spring hook) depend on the market.

### 9.1 Shoulder Strap




- ▶ Put on the shoulder strap (1).
- ▶ Adjust the length of the strap so that the carabiner (2) is about a hand's width below your right hip.

### 9.2 Full Harness




- ▶ Put on the full harness (1).
- ▶ Adjust the length of the strap so that the carabiner (2) is about a hand's width below your right hip.
- ▶ Close the locking plate (3).

### 9.3 Attaching Machine to Harness



- ▶ Attach the carabiner (1) to the carrying ring (2) on the drive tube – hold the carrying ring steady.

## 9.4 Disconnecting Machine from Harness



- ▶ Press down the bar on the carabiner (1) and pull the carrying ring (2) out of the carabiner.

## 9.5 Throwing Off the Machine

### ! WARNING

The machine must be quickly thrown off in the event of imminent danger. Practice removing and putting down the machine as you would in an emergency. To avoid damage, do not throw the machine to the ground when practicing.

Practice quickly detaching the power tool from the carabiner as described under "Disconnecting Machine from Harness".



If you are using a shoulder strap: Practice slipping the strap off your shoulder.

If you are using a full harness: Practice quickly opening the locking plate and slipping the harness straps off your shoulders.

## 10 Starting / Stopping the Engine

### 10.1 Starting the Engine

Always follow the operating instructions for the KombiEngine and basic power tool.



- ▶ Place the machine on the ground so that it rests securely on the engine support and the gearbox.
- ▶ On models with an adjustable cutter bar: Set the cutter bar to the straight (0°) position.
- ▶ Remove the blade scabbard.

**To reduce the risk of accidents**, check that the cutting blades are not touching the ground of any other obstacles.

- ▶ If necessary, rest the gearbox on a raised support (e.g. mound, brick or something similar).
- ▶ Make sure you have a firm footing, either standing, stooping or kneeling.
- ▶ Hold the machine with you left hand and press it down **firmly** – do not touch the controls on the control handle – see KombiEngine or basic power tool instruction manual.

### NOTICE

Do not stand or kneel on the drive tube.

### ! WARNING

The cutting attachment may begin to move as soon as the engine starts. For this reason, blip the throttle after starting – the engine returns to idling speed.

The starting procedure is now as described in the instruction manual of the KombiEngine or basic power tool you are using.

### 10.2 Stopping the Engine


- ▶ See KombiEngine or basic power tool instruction manual.

## 11 Lubricating the Gearbox



### 11.1 Blade Drive Gear

Lubricate the blade drive gear with STIHL gear lubricant for hedge trimmers – see "Special Accessories".



- ▶ Check the lubricant level at regular intervals of about every 25 hours of operation. Unscrew the filler plug (1) – if no grease can be seen on the inside of the filler plug, screw the tube of grease into the filler hole.
- ▶ Squeeze up to 10 g (2/5 oz) grease into the gearbox.


#### NOTICE

Do not completely fill the gearbox with grease.

- ▶ Unscrew the tube of grease from the filler hole.
- ▶ Refit the filler plug and tighten it down firmly.

### 11.2 Angle Drive Gear

Lubricate the angle drive gear with STIHL gear lubricant for brushcutters (special accessory).



- ▶ Check the lubricant level at regular intervals of about every 25 hours of operation. Unscrew the filler plug (2) – if no grease can be seen on the inside of the filler plug, screw the tube of grease into the filler hole.
- ▶ Squeeze up to 5 g (1/5 oz) grease into the gearbox.

#### NOTICE

Do not completely fill the gearbox with grease.

- ▶ Unscrew the tube of grease from the filler hole.
- ▶ Refit the filler plug and tighten it down firmly.

## 12 Storing the Machine

For periods of 30 days or longer

- ▶ Clean the cutting blades, check condition and spray them with STIHL resin solvent.
- ▶ Fit the blade scabbard.
- ▶ If the KombiTool is removed from the KombiEngine and stored separately: Fit the protective cap on the drive tube to protect it from dust and dirt.
- ▶ Store the machine in a dry and secure location. Keep out of the reach of children and other unauthorized persons.

## 13 Maintenance and Care

The following intervals apply to normal operating conditions only. If your daily working time is longer or operating conditions are difficult (very dusty work area, etc.), shorten the specified intervals accordingly.

#### All accessible screws and nuts

- ▶ Check and retighten if necessary (not screws and nuts on cutting blades)

#### Cutting blades

- ▶ Visual inspection before starting work
- ▶ Resharpener as necessary
- ▶ Replace if damaged

#### Gearbox lubrication

- ▶ Check before starting work
- ▶ Replenish as necessary

#### Safety labels

- ▶ Replace illegible safety labels

## 14 Sharpening Instructions

When cutting performance and behavior begin to deteriorate, i.e. blades frequently snag on branches: Resharpener the cutting blades.

It is best to have the cutting blades resharpened by a dealer on a workshop sharpener. STIHL recommends a STIHL servicing dealer.

**NOTICE**

Do not operate your machine with dull or damaged cutting blades. This may cause overload and will give unsatisfactory cutting results.

## 15 Minimize Wear and Avoid Damage

Observing the instructions in this manual and the KombiEngine manual helps reduce the risk of unnecessary wear and damage to the power tool.

The power tool must be operated, maintained and stored with the due care and attention described in these instruction manuals.

The user is responsible for all damage caused by non-observance of the safety precautions, operating and maintenance instructions. This includes in particular:

- Alterations or modifications to the product not approved by STIHL.
- Using tools or accessories which are neither approved or suitable for the product or are of a poor quality.
- Using the product for purposes for which it was not designed.
- Using the product for sports or competitive events.
- Consequential damage caused by continuing to use the product with defective components.

### 15.1 Maintenance Work

All the operations described in the chapter on "Maintenance and Care" must be performed on a regular basis. If these maintenance operations cannot be performed by the owner, they should be performed by a servicing dealer.

STIHL recommends that you have servicing and repair work carried out exclusively by an authorized STIHL servicing dealer. STIHL dealers are regularly given the opportunity to attend training courses and are supplied with the necessary technical information.


If these maintenance operations are not carried out as specified, the user assumes responsibility for any damage that may occur. Among other parts, this includes:

- Corrosion and other consequential damage resulting from improper storage.
- Damage to the product resulting from the use of poor quality replacement parts.

## 15.2 Parts Subject to Wear and Tear

Some parts of the power tool (e.g. cutting blades) are subject to normal wear and tear even during regular operation in accordance with instructions and, depending on the type and duration of use, have to be replaced in good time.

## 16 Main Parts



- 1 Blade drive gear
- 2 Angle drive
- 3 Sliding sleeve
- 4 Drive tube
- 5 Quadrant
- 6 Adjusting lever
- 7 Blade guard (scabbard)
- 8 Cap

## 17 Specifications

### 17.1 Cutting blades

Type:	Double-edged for bidirectional cutting
Cutting length:	250 mm
Tooth spacing:	34 mm
Tooth height:	22 mm
Sharpening angle:	45° to horizontal

### 17.2 Weight

FH-KM:	2.1 kg
--------	--------

### 17.3 Noise and vibration values

Sound and vibration data measurements on power tools with the FH-KM KombiTool include idling and rated maximum speed with the same duration of exposure.

For further details on compliance with Vibration Directive 2002/44/EC, see

[www.stihl.com/vib](http://www.stihl.com/vib)

### 17.3.1 Sound pressure level $L_{peq}$ in accordance with ISO 22868

KM 56 R:	92 dB(A)
KM 85 R:	96 dB(A)
KM 94 R:	92 dB(A)
KM 111 R:	96 dB(A)
KM 131:	97 dB(A)
KM 131 R:	97 dB(A)
KMA 130 R:	79 dB(A)
KMA 135 R:	78.4 dB(A)
KMA 80.0 R:	80 dB(A)
KMA 120.0 R:	80 dB(A)
KMA 200.0 R:	79 dB(A)
FR 131 T:	97 dB(A)

### 17.3.2 Sound power level $L_{weq}$ in accordance with ISO 3744

KM 56 R:	102 dB(A)
KM 85 R:	109 dB(A)
KM 94 R:	104 dB(A)
KM 111 R:	105 dB(A)
KM 131:	107 dB(A)
KM 131 R:	105 dB(A)
KMA 130 R:	94 dB(A)
KMA 135 R:	91.3 dB(A)
KMA 80.0 R:	92 dB(A)
KMA 120.0 R:	92 dB(A)
KMA 200.0 R:	93 dB(A)
FR 131 T:	107 dB(A)

### 17.3.3 Vibration level $a_{hv,eq}$ in accordance with ISO 22867

	Handle, left	Handle, right
KM 56 R:	5.6 m/s <sup>2</sup>	5.8 m/s <sup>2</sup>
KM 85 R:	3.5 m/s <sup>2</sup>	4.2 m/s <sup>2</sup>
KM 94 R:	3.1 m/s <sup>2</sup>	3.9 m/s <sup>2</sup>
KM 111 R:	4.4 m/s <sup>2</sup>	2.7 m/s <sup>2</sup>
KM 131:	2.3 m/s <sup>2</sup>	2.9 m/s <sup>2</sup>
KM 131 R:	4.7 m/s <sup>2</sup>	3.3 m/s <sup>2</sup>
KMA 130 R:	2.5 m/s <sup>2</sup>	2.2 m/s <sup>2</sup>
KMA 135 R:	2.1 m/s <sup>2</sup>	2.4 m/s <sup>2</sup>
KMA 80.0 R:	2.7 m/s <sup>2</sup>	2.0 m/s <sup>2</sup>
KMA 120.0 R:	2.7 m/s <sup>2</sup>	2.0 m/s <sup>2</sup>
KMA 200.0 R:	2.6 m/s <sup>2</sup>	2.2 m/s <sup>2</sup>
FR 131 T:	1.8 m/s <sup>2</sup>	1.7 m/s <sup>2</sup>

The K-factor in accordance with Directive 2006/42/EC is 2.0 dB(A) for the sound pressure level and sound power level; the K-factor in accordance with Directive 2006/42/EC is 2.0 m/s<sup>2</sup> for the vibration level.

## 17.4 REACH

REACH is an EC regulation and stands for the Registration, Evaluation, Authorization and Restriction of Chemical substances.

For information on compliance with the REACH regulation (EC) No. 1907/2006 see

[www.stihl.com/reach](http://www.stihl.com/reach)

## 18 Maintenance and Repairs

Users of this machine may only carry out the maintenance and service work described in this user manual. All other repairs must be carried out by a servicing dealer.

STIHL recommends that you have servicing and repair work carried out exclusively by an authorized STIHL servicing dealer. STIHL dealers are regularly given the opportunity to attend training courses and are supplied with the necessary technical information.

When repairing the machine, only use replacement parts which have been approved by STIHL for this power tool or are technically identical. Only use high-quality replacement parts in order to avoid the risk of accidents and damage to the machine.


STIHL recommends the use of original STIHL replacement parts.

Original STIHL parts can be identified by the STIHL part number, the **STIHL** logo and the STIHL parts symbol  (the symbol may appear alone on small parts).

## 19 Disposal

Contact the local authorities or your STIHL servicing dealer for information on disposal.

Improper disposal can be harmful to health and pollute the environment.



- ▶ Take STIHL products including packaging to a suitable collection point for recycling in accordance with local regulations.
- ▶ Do not dispose with domestic waste.

## 20 EC Declaration of Conformity

ANDREAS STIHL AG & Co. KG  
Badstr. 115

D-71336 Waiblingen

Germany

declares under its sole responsibility that

Designation: Scrub cutter KombiTool  
 Make: STIHL  
 Series: FH-KM  
 Serial identification number: 4243

conforms to the relevant provisions of Directive 2006/42/EC and has been developed and manufactured in compliance with the following standards in the versions valid on the date of production:

EN ISO 12100, EN ISO 11806-1 (in conjunction with the specified KM models)

EN ISO 12100, EN 60745-1, EN 60745-2-15 (in conjunction with KMA 130 R)

EN ISO 12100, EN 62841-1, EN 62841-4-2 (in conjunction with KMA 135 R, KMA 80.0 R, KMA 120.0 R, KMA 200.0 R)

EN ISO 12100, EN ISO 11806-1 (in conjunction with the specified FR models)

Technical documents deposited at:

ANDREAS STIHL AG & Co. KG  
 Produktzulassung

The year of manufacture is specified on the power tool.

Waiblingen, 2023-12-01

ANDREAS STIHL AG & Co. KG

pp



Robert Olma, Vice President, Regulatory Affairs & Global Governmental Relations



## 21 UKCA Declaration of Conformity

ANDREAS STIHL AG & Co. KG  
 Badstr. 115  
 D-71336 Waiblingen

Germany

declares under its sole responsibility that

Designation: Scrub cutter KombiTool

Make: STIHL  
 Series: FH-KM  
 Serial identification number: 4243

conforms to the relevant provisions of the UK Supply of Machinery (Safety) Regulations 2008 and has been manufactured in compliance with the following standards in the versions valid on the date of production:

EN ISO 12100, EN ISO 11806-1 (in conjunction with the specified KM models)

EN ISO 12100, EN 60745-1, EN 60745-2-15 (in conjunction with KMA 130 R)

EN ISO 12100, EN 62841-1, EN 62841-4-2 (in conjunction with KMA 135 R, KMA 80.0 R, KMA 120.0 R, KMA 200.0 R)

EN ISO 12100, EN ISO 11806-1 (in conjunction with the specified FR models)

Technical documents deposited at:

ANDREAS STIHL AG & Co. KG

The year of manufacture is indicated on the power tool.

Waiblingen, 2023-12-01

ANDREAS STIHL AG & Co. KG

pp



Robert Olma, Vice President, Regulatory Affairs & Global Governmental Relations



22 Addresses

[www.stihl.com](http://www.stihl.com)



[www.stihl.com](http://www.stihl.com)



0458-476-0121-D



0458-476-0121-D