



No measures are required.  
 Useable with measures.  
 Reduce exposure duration.

model	daily exposure time [h]	time sequence operating mode (idling/ full load/ nom. speed)	standard	equivalent vibration level handle left a hv,eq [m/s <sup>2</sup> ]	equivalent vibration level handle right a hv,eq [m/s <sup>2</sup> ]	daily vibration exposure handle left A(8) [m/s <sup>2</sup> ]	daily vibration exposure handle right A(8) [m/s <sup>2</sup> ]
FSA 130	3,5	HD	EN 50636-2-91	1,9	1,1	1,3	0,7
FSA 130 R	3,5	HD	EN 50636-2-91	3,5	3,3	2,3	2,2
FSA 45	1,0	HD	EN 50636-2-91	1,7	4,9	0,5	1,7
FSA 56	1,0	HD	EN 50636-2-91	3,5	3,5	1,2	1,2
FSA 65	1,0	HD	EN 50636-2-91	1,3	1,1	0,5	0,4
FSA 85	1,0	HD	EN 50636-2-91	1,4	0,8	0,5	0,3
FSA 90	1,0	HD	EN 50636-2-91	3,5	3,5	1,2	1,2
FSA 90 R	1,0	HD	EN 50636-2-91	4,8	3,5	1,7	1,2

All data is subject to change and applicable to European versions only.